

Hello Computers CCIE Security Lab Solution for Lab12

r1config

```
r1#
hostname r1
!
service password-encryption
logging buffered 10000 7
logging 150.50.15.101
logging facility local6
no service tcp-small-server
no service udp-small-server
no service finger
service debug timestamp
no ntp enable
no cdp run
ip http server
ip http access-class 10
access-list 10 permit 150.50.0.0 0.0.255.255
snmp-server community hello ro 71
snmp-server community hellorw rw 72
snmp-server contact Hello Computers
snmp-server location Fremont-Santa Clara
access-list 71 permit 150.50.0.0 0.0.255.255
access-list 72 permit 150.50.111.0 0.0.0.255
scheduler interval 1000
no ip domain-lookup
no ip source-route
!
!acl for icmp rate-limiting
access-list 141 permit icmp any any
access-list 141 deny ip any any
!
!deny Trinoo
access-list 171 deny tcp any any eq 27665
access-list 171 deny udp any any eq 31335
access-list 171 deny udp any any eq 26444
!deny Stacheldraht
access-list 171 deny tcp any any eq 16660
access-list 171 deny tcp any any eq 65000
!deny subseven
access-list 171 deny tcp any any eq 6711
access-list 171 deny tcp any any eq 6712
access-list 171 deny tcp any any eq 6669
access-list 171 deny tcp any any eq 2222
access-list 171 deny tcp any any eq 7000
access-list 171 permit ip any any
!
enable secret hello
!
int e0
no ip directed-broadcast
```

```
no ip proxy-arp
no ip redirects
no ip icmp mask-reply
no ip icmp unreachable
no ip route-cache
rate-limit output access-group 141 1000000 512000 786000 conform-action transmit exceed-action drop
ip access-group 171 out

ip add 150.50.15.1 255.255.255.0
ip ospf priority 1
no shut
ip ospf authentication message-digest
ip ospf message-digest key 1 md5 hello
!
int s0
encapsulation frame
frame-relay lmi-type ansi
no shut
!
int s0.14 point-to-point
ip add 150.50.14.1 255.255.255.0
frame interface-dlci 114
ip ospf network point-to-point
ip ospf authentication message-digest
ip ospf message-digest key 1 md5 hello
crypto map supermap
!
int s0.123 multipoint
ip add 150.50.123.1 255.255.255.0
frame map ip 150.50.123.2 112 broadcast
frame map ip 150.50.123.3 113 broadcast
ip ospf network point-to-multipoint
ip ospf authentication message-digest
ip ospf message-digest key 1 md5 hello
crypto map supermap
!
int lo0
ip add 11.11.11.11 255.255.255.0
!
int lo1
ip add 111.111.111.111 255.255.255.0
!
router ospf 100
network 150.50.15.0 0.0.0.255 area 1
network 11.11.11.0 0.0.0.255 area 1
network 150.50.14.0 0.0.0.255 area 1
network 150.50.123.0 0.0.0.255 area 0
area 1 virtual 44.44.44.44 authentication message-digest
area 1 virtual 44.44.44.44 message-digest-key 1 md5 hello
area 0 authentication message-digest
area 1 authentication message-digest
distribute-list 11 in
!
```

```

router bgp 4799
network 111.111.111.0 mask 255.255.255.0
no auto-summary
no sync
neighbor 33.33.33.33 remote-as 4799
neighbor 33.33.33.33 description r3lo0-ibgp
neighbor 33.33.33.33 update-source loopabck 0
neighbor 33.33.33.33 soft-reconfiguration in
neighbor 33.33.33.33 password hello
neighbor 150.50.15.111 remote-as 111
neighbor 150.50.15.111 description AS111-bb1
neighbor 150.50.15.111 update-source loopabck 0
neighbor 150.50.15.111 soft-reconfiguration in
neighbor 150.50.15.111 ebgp-multihop 10
neighbor 150.50.15.111 route-map setnh in
aggregate-address 201.201.0.0 255.255.240.0
aggregate-address 201.201.16.0 255.255.252.0
!
route-map setnh permit 10
set ip next-hop 150.50.15.111
!
access-list 11 deny 192.168.66.0 0.0.0.255
access-list 11 permit any
!
ip domain-name hellocomputers.com
ip host caserver 150.50.15.100
!
crypto key generate rsa
!
crypto ca identity caserver
enrollment mode ra
enrollment url http://caserver/certsrv/mscep/mscep.dll
!
crypto ca authenticate caserver
crypto ca enroll caserver
!
crypto isakmp policy 10
authentication rsa-sig
hash md5
!
crypto ipsec transform-set tset esp-des esp-sha-hmac
!
crypto map supermap 10 ipsec-isakmp
set peer 22.22.22.22
set transform-set tset
match address 112
!
access-list 112 permit ip host 150.50.15.150 host 150.50.24.150
!
line con 0
no login
line vty 0 4
login

```

password hello

r2config

r2#

hostname r2

!

service password-encryption

logging buffered 10000 7

logging 150.50.15.101

logging facility local6

no service tcp-small-server

no service udp-small-server

no service finger

service debug timestamp

no ntp enable

no cdp run

ip http server

ip http access-class 10

access-list 10 permit 150.50.0.0 0.0.255.255

snmp-server community hello ro 71

snmp-server community hellorw rw 72

snmp-server contact Hello Computers

snmp-server location Fremont-Santa Clara

access-list 71 permit 150.50.0.0 0.0.255.255

access-list 72 permit 150.50.111.0 0.0.0.255

scheduler interval 1000

no ip domain-lookup

no ip source-route

!

!acl for icmp rate-limiting

access-list 141 permit icmp any any

access-list 141 deny ip any any

!

!deny Trinoo

access-list 171 deny tcp any any eq 27665

access-list 171 deny udp any any eq 31335

access-list 171 deny udp any any eq 26444

!deny Stacheldraht

access-list 171 deny tcp any any eq 16660

access-list 171 deny tcp any any eq 65000

!deny subseven

access-list 171 deny tcp any any eq 6711

access-list 171 deny tcp any any eq 6712

access-list 171 deny tcp any any eq 6669

access-list 171 deny tcp any any eq 2222

access-list 171 deny tcp any any eq 7000

access-list 171 permit ip any any

!

enable secret hello

!

int e0

no ip directed-broadcast

```

no ip proxy-arp
no ip redirects
no ip icmp mask-reply
no ip icmp unreachable
no ip route-cache
rate-limit output access-group 141 1000000 512000 786000 conform-action transmit exceed-action drop
ip access-group 171 out
ip add 150.50.24.2 255.255.255.0
no shut
ip rip authentication mode md5
ip rip authentication key-chain keyr2
!
int s0
encapsulation frame
frame-relay lmi-type ansi
ip add 150.50.123.2 255.255.255.0
frame map ip 150.50.123.1 121 broadcast
frame map ip 150.50.123.3 121 broadcast
ip ospf network point-to-multipoint
ip ospf authentication message-digest
ip ospf message-digest key 1 md5 hello
ip ospf priority 1
crypto map supermap
no shut
!
int lo0
ip add 22.22.22.22 255.255.255.0
!
int lo1
ip add 122.122.122.122 255.255.255.0
!
key chain keyr2
key 1
  key-string hello
!
router ospf 100
network 150.50.123.0 0.0.0.255 area 0
network 22.22.22.0 0.0.0.255 area 0
redistribute rip subnets
area 0 authentication message-digest
distribute-list 11 in
!
router rip
no auto-summary
version 2
network 150.50.24.0 0.0.0.255
redistribute ospf 100
default-metric 2
!
router bgp 4799
network 122.122.122.0 mask 255.255.255.0
no auto-summary
no sync

```

```
neighbor 33.33.33.33 remote-as 4799
neighbor 33.33.33.33 description r1l0-ibgp
neighbor 33.33.33.33 soft-reconfiguration in
neighbor 33.33.33.33 update-source loopback 0
neighbor 33.33.33.33 password hello
neighbor 150.50.24.112 description AS112-bb2
neighbor 150.50.24.112 soft-reconfiguration in
neighbor 150.50.24.112 ebgp-multihop 10
neighbor 150.50.24.112 route-map setnh in
neighbor 150.50.24.112 filter-list 20 out
aggregate-address 202.202.0.0 255.255.240.0
aggregate-address 202.202.16.0 255.255.252.0
!
route-map setnh permit 10
set ip next-hop 150.50.24.112
!
ip as-path access-list 20 deny _111_
ip as-path access-list 20 permit .*
!
access-list 11 deny 192.168.66.0 0.0.0.255
access-list 11 permit any
!
ip domain-name hellocomputers.com
ip host caserver 150.50.15.100
!
crypto key generate rsa
!
crypto ca identity caserver
enrollment mode ra
enrollment url http://caserver/certsrv/mscep/mscep.dll
!
crypto ca authenticate caserver
crypto ca enroll caserver
!
crypto isakmp policy 10
authentication rsa-sig
hash md5
!
crypto ipsec transform-set tset esp-des esp-sha-hmac
!
crypto map supermap 10 ipsec-isakmp
set peer 11.11.11.11
set transform-set tset
match address 121
!
access-list 121 permit ip host 150.50.24.150 host 150.50.15.150
!
line con 0
no login
line vty 0 4
login
password hello
```

r3config

```
-----
r3#
hostname r3
!
service password-encryption
logging buffered 10000 7
logging 150.50.15.101
logging facility local6
no service tcp-small-server
no service udp-small-server
no service finger
service debug timestamp
no ntp enable
no cdp run
ip http server
ip http access-class 10
access-list 10 permit 150.50.0.0 0.0.255.255
snmp-server community hello ro 71
snmp-server community hellorw rw 72
snmp-server contact Hello Computers
snmp-server location Fremont-Santa Clara
access-list 71 permit 150.50.0.0 0.0.255.255
access-list 72 permit 150.50.111.0 0.0.0.255
scheduler interval 1000
no ip domain-lookup
no ip source-route
!
!acl for icmp rate-limiting
access-list 141 permit icmp any any
access-list 141 deny ip any any
!
!deny Trinoo
access-list 171 deny tcp any any eq 27665
access-list 171 deny udp any any eq 31335
access-list 171 deny udp any any eq 26444
!deny Stacheldraht
access-list 171 deny tcp any any eq 16660
access-list 171 deny tcp any any eq 65000
!deny subseven
access-list 171 deny tcp any any eq 6711
access-list 171 deny tcp any any eq 6712
access-list 171 deny tcp any any eq 6669
access-list 171 deny tcp any any eq 2222
access-list 171 deny tcp any any eq 7000
access-list 171 permit ip any any
!
enable secret hello
!
int e0
no ip directed-broadcast
no ip proxy-arp
no ip redirects
```

```

no ip icmp mask-reply
no ip icmp unreachable
no ip route-cache
rate-limit output access-group 141 1000000 512000 786000 conform-action transmit exceed-action drop
ip access-group 171 out
ip add 150.50.33.3 255.255.255.0
no shut
crypto map clientmap
!
int s0
encapsulation frame
frame-relay lmi-type ansi
ip address 150.50.123.3 255.255.255.0
ip ospf network point-to-multipoint
frame map ip 150.50.123.1 131 broadcast
frame map ip 150.50.123.2 131 broadcast
ip ospf authentication message-digest
ip ospf message-digest key 1 md5 hello
ip ospf priority 1
no shut
!
int atm0
ip address 150.50.113.3
atm pvc 1 0 5 qsaal
atm pvc 2 0 16 ilmi
atm pvc 3 4 40 aal5snap
map-group map1
no shut
!
int lo0
ip add 33.33.33.33 255.255.255.0
!
int lo1
ip add 133.133.133.133 255.255.255.0
!
router ospf 100
network 150.50.123.0 0.0.0.255 area 0
network 33.33.33.0 0.0.0.255 area 0
network 150.50.33.0 0.0.0.255 area 0
network 150.50.3.0 0.0.0.255 area 0
area 0 authentication message-digest
distribute-list 11 in
!
router bgp 4799
network 133.133.133.0 mask 255.255.255.0
no auto-summary
no sync
neighbor 11.11.11.11 remote-as 4799
neighbor 11.11.11.11 description r1lo0-ibgp
neighbor 11.11.11.11 soft-reconfiguration in
neighbor 11.11.11.11 update-source loopback 0
neighbor 11.11.11.11 route-reflector-client
neighbor 11.11.11.11 password hello

```



```

neighbor 22.22.22.22 remote-as 4799
neighbor 22.22.22.22 description r2lo0-ibgp
neighbor 22.22.22.22 soft-reconfiguration in
neighbor 22.22.22.22 update-source loopback 0
neighbor 22.22.22.22 route-reflector-client
neighbor 22.22.22.22 password hello
neighbor 150.50.3.113 remote-as 113
neighbor 150.50.3.113 description bb3atm0-AS113
neighbor 150.50.3.113 soft-reconfiguration in
neighbor 150.50.3.113 route-map lab12-1-20 in
neighbor 150.50.3.113 default-originate
!
route-map lab12-1-20 permit 10
set metric 113
set local-preference 113
!
map-list map1
ip 150.50.3.113 atm-vc 3 broadcast
!
access-list 11 deny 192.168.66.0 0.0.0.255
access-list 11 permit any
!
ip local pool pool1 192.168.1.1 192.168.1.254
crypto isakmp policy 10
hash md5
authentication pre-share
!
crypto isakmp key hello123 address 0.0.0.0
crypto isakmp client configuration address-pool local pool1
crypto ipsec transform-set tsetclient esp-des
!
crypto dynamic-map dmap 10
set transform-set tsetclient
!
crypto map clientmap client configuration address initiate
crypto map clientmap client configuration address respond
crypto map clientmap 10 ipsec-isakmp dynamic dmap
!
line con 0
no login
line vty 0 4
login
password hello

r4config
-----
r4#
hostname r4
!
service password-encryption
logging buffered 10000 7
logging 150.50.15.101
logging facility local6

```

```

no service tcp-small-server
no service udp-small-server
no service finger
service debug timestamp
no ntp enable
no cdp run
ip http server
ip http access-class 10
access-list 10 permit 150.50.0.0 0.0.255.255
snmp-server community hello ro 71
snmp-server community hellorw rw 72
snmp-server contact Hello Computers
snmp-server location Fremont-Santa Clara
access-list 71 permit 150.50.0.0 0.0.255.255
access-list 72 permit 150.50.111.0 0.0.0.255
scheduler interval 1000
no ip domain-lookup
no ip source-route
!
!acl for icmp rate-limiting
access-list 141 permit icmp any any
access-list 141 deny ip any any
!
!deny Trinoo
access-list 171 deny tcp any any eq 27665
access-list 171 deny udp any any eq 31335
access-list 171 deny udp any any eq 26444
!deny Stacheldraht
access-list 171 deny tcp any any eq 16660
access-list 171 deny tcp any any eq 65000
!deny subseven
access-list 171 deny tcp any any eq 6711
access-list 171 deny tcp any any eq 6712
access-list 171 deny tcp any any eq 6669
access-list 171 deny tcp any any eq 2222
access-list 171 deny tcp any any eq 7000
access-list 171 permit ip any any
!
enable secret hello
isdn switch-type basic-ni
username r5 password hello
!
int e0
no ip directed-broadcast
no ip proxy-arp
no ip redirects
no ip icmp mask-reply
no ip icmp unreachable
no ip route-cache
rate-limit output access-group 141 1000000 512000 786000 conform-action transmit exceed-action drop
ip access-group 171 out
ip add 150.50.24.4 255.255.255.0
no shut

```

```

!
int s0
encapsulation frame
frame-relay lmi-type ansi
ip address 150.50.14.4 255.255.255.0
ip ospf network point-to-point
frame-relay interface-dlci 141
ip ospf authentication message-digest
ip ospf message-digest key 1 md5 hello
crypto map supermap
no shut
!
int s1
encapsulation frame
frame-relay lmi-type ansi
ip address 150.50.46.4 255.255.255.0
frame route ip 150.50.46.6 146 broadcast
no shut
ip authentication mode eigrp 46 md5
ip authentication key-chain eigrp 46 keyr4
!
int bri0
ip add 145.45.45.4 255.255.255.240
isdn switch-type basic-ni
dialer-group 1
encapsulation ppp
ppp authentication chap
dialer idle-timeout 60
dialer load-threshold 128 either
ppp multilink
ppp callback accept
dialer callback-secure
dialer map ip 145.45.45.5 class callbackclass name r5 broadcast 8358662
dialer map ip 145.45.45.5 class callbackclass name r5 broadcast 8358664
ip ospf demand-circuit
ip ospf network point-to-point
no shut
ip ospf authentication message-digest
ip ospf message-digest key 1 md5 hello
crypto map supermap
!
int lo0
ip add 44.44.44.44 255.255.255.0
!
router ospf 100
network 150.50.14.0 0.0.0.255 area 1
network 150.50.24.0 0.0.0.255 area 1
network 44.44.44.0 0.0.0.255 area 1
network 145.45.45.0 0.0.0.15 area 1
network 150.50.46.0 0.0.0.255 area 2
area 1 authentication message-digest
area 2 authentication message-digest
distribute-list 11 in

```

```

!
dialer-list 1 protocol ip permit
!
map-class dialer callbackclass
  dialer callback-server username
!
access-list 11 deny 192.168.66.0 0.0.0.255
access-list 11 permit any
!
ip domain-name hellocomputers.com
ip host caserver 150.50.15.100
!
crypto key generate rsa
!
crypto ca identity caserver
  enrollment mode ra
  enrollment url http://caserver/certsrv/mscep/mscep.dll
!
crypto ca authenticate caserver
crypto ca enroll caserver
!
crypto isakmp policy 10
  authentication rsa-sig
  hash md5
!
crypto ipsec transform-set tset esp-des esp-sha-hmac
!
crypto map supermap 10 ipsec-isakmp
  set peer 55.55.55.55
  set transform-set tset
  match address 145
!
access-list 145 permit ip host 150.50.24.150 host 150.50.15.150
!
line con 0
  no login
line vty 0 4
  login
  password hello

r5config
-----
r5#
hostname r5
!
service password-encryption
logging buffered 10000 7
logging 150.50.15.101
logging facility local6
no service tcp-small-server
no service udp-small-server
no service finger
service debug timestamp

```

```
no ntp enable
no cdp run
ip http server
ip http access-class 10
access-list 10 permit 150.50.0.0 0.0.255.255
snmp-server community hello ro 71
snmp-server community hellorw rw 72
snmp-server contact Hello Computers
snmp-server location Fremont-Santa Clara
access-list 71 permit 150.50.0.0 0.0.255.255
access-list 72 permit 150.50.111.0 0.0.0.255
scheduler interval 1000
no ip domain-lookup
no ip source-route
!
!acl for icmp rate-limiting
access-list 141 permit icmp any any
access-list 141 deny ip any any
!
!deny Trinoo
access-list 171 deny tcp any any eq 27665
access-list 171 deny udp any any eq 31335
access-list 171 deny udp any any eq 26444
!deny Stacheldraht
access-list 171 deny tcp any any eq 16660
access-list 171 deny tcp any any eq 65000
!deny subseven
access-list 171 deny tcp any any eq 6711
access-list 171 deny tcp any any eq 6712
access-list 171 deny tcp any any eq 6669
access-list 171 deny tcp any any eq 2222
access-list 171 deny tcp any any eq 7000
access-list 171 permit ip any any
!
enable secret hello
isdn switch-type basic-ni
username r4 password hello
!
int e0
no ip directed-broadcast
no ip proxy-arp
no ip redirects
no ip icmp mask-reply
no ip icmp unreachable
no ip route-cache
rate-limit output access-group 141 1000000 512000 786000 conform-action transmit exceed-action drop
ip access-group 171 out
ip add 150.50.15.5 255.255.255.0
ip ospf priority 1
no shut
ip ospf authentication message-digest
ip ospf message-digest key 1 md5 hello
!
```

```

int s0
encapsulation hdlc
ip address 150.50.57.5 255.255.255.0
no shut
!
int bri0
ip add 145.45.45.5 255.255.255.240
isdn switch-type basic-ni
dialer-group 1
encapsulation ppp
ppp authentication chap
dialer idle-timeout 60
dialer load-threshold 128 either
ppp multilink
ppp callback request
dialer map ip 145.45.45.4 name r4 broadcast 8358661
dialer map ip 145.45.45.4 name r4 broadcast 8358663
ip ospf demand-circuit
ip ospf network point-to-point
no shut
ip ospf authentication message-digest
ip ospf message-digest key 1 md5 hello
crypto map supermap
!
int lo0
ip add 55.55.55.55 255.255.255.0
!
router ospf 100
network 150.50.15.0 0.0.0.255 area 1
network 55.55.55.0 0.0.0.255 area 1
network 145.45.45.0 0.0.0.15 area 1
area 1 authentication message-digest
redistribute eigrp 57 subnets
distribute-list 11 in
!
router eigrp 57
no auto-summary
network 150.50.57.0 0.0.0.255
passive bri0
redistribute ospf 100 metric 10000 100 255 1 1500
distribute-list 12 in
!
dialer-list 1 protocol ip permit
!
aaa new-model
tacacs-server host 150.50.15.100 key hello
aaa authentication login no_authentication none
aaa authorization exec no_authorization none
aaa authorization commands no_authorization none
aaa authentication login lab12-2-2 group tacacs
aaa authorization exec lab12-2-2 group tacacs
aaa authorization commands lab12-2-2 group tacacs
aaa accounting commands 0 lab12-2-2 start-stop tacacs

```

```

ip tacacs source-interface loopback0
!
access-list 11 deny 192.168.66.0 0.0.0.255
access-list 11 permit any
access-list 12 deny 10.10.77.0 0.0.0.255
access-list 12 permit any
!
ip domain-name hellocomputers.com
ip host caserver 150.50.15.100
!
crypto key generate rsa
!
crypto ca identity caserver
  enrollment mode ra
  enrollment url http://caserver/certsrv/mscep/mscep.dll
!
crypto ca authenticate caserver
crypto ca enroll caserver
!
crypto isakmp policy 10
  authentication rsa-sig
  hash md5
!
crypto ipsec transform-set tset esp-des esp-sha-hmac
!
crypto map supermap 10 ipsec-isakmp
  set peer 44.44.44.44
  set transform-set tset
  match address 145
!
access-list 145 permit ip host 150.50.15.150 host 150.50.24.150
!
line con 0
  login authentication no_authentication
  authorization exec no_authorization
  authorization commands no_authorization
line vty 0 4
  login authentication lab12-2-2
  authorization exec lab12-2-2
  authorization commands lab12-2-2
  accounting commands 0 lab12-2-2
!

r6config
-----
r6#
hostname r6
!
service password-encryption
logging buffered 10000 7
logging 150.50.15.101
logging facility local6
no service tcp-small-server

```

```
no service udp-small-server
no service finger
service debug timestamp
no ntp enable
no cdp run
ip http server
ip http access-class 10
access-list 10 permit 150.50.0.0 0.0.255.255
snmp-server community hello ro 71
snmp-server community hellorw rw 72
snmp-server contact Hello Computers
snmp-server location Fremont-Santa Clara
access-list 71 permit 150.50.0.0 0.0.255.255
access-list 72 permit 150.50.111.0 0.0.0.255
scheduler interval 1000
no ip domain-lookup
no ip source-route
!
!acl for icmp rate-limiting
access-list 141 permit icmp any any
access-list 141 deny ip any any
!
!deny Trinoo
access-list 171 deny tcp any any eq 27665
access-list 171 deny udp any any eq 31335
access-list 171 deny udp any any eq 26444
!deny Stacheldraht
access-list 171 deny tcp any any eq 16660
access-list 171 deny tcp any any eq 65000
!deny subseven
access-list 171 deny tcp any any eq 6711
access-list 171 deny tcp any any eq 6712
access-list 171 deny tcp any any eq 6669
access-list 171 deny tcp any any eq 2222
access-list 171 deny tcp any any eq 7000
access-list 171 permit ip any any
!
enable secret hello
!
int e0
no ip directed-broadcast
no ip proxy-arp
no ip redirects
no ip icmp mask-reply
no ip icmp unreachable
no ip route-cache
rate-limit output access-group 141 1000000 512000 786000 conform-action transmit exceed-action drop
ip access-group 171 out
ip add 192.168.66.6 255.255.255.0
no shut
ip nat inside
!
int s0
```



```

encapsulation frame
frame-relay lmi-type ansi
ip address 150.50.46.6 255.255.255.0
no shut
ip nat outside
!
int lo0
ip add 66.66.66.66 255.255.255.0
!
int lo2
ip add 168.168.168.1 255.255.255.240
!
int lo3
ip add 168.168.168.17 255.255.255.240
!
int lo4
ip add 168.168.168.33 255.255.255.240
!
int lo5
ip add 168.168.168.49 255.255.255.240
!
router ospf 100
network 150.50.46.0 0.0.0.255 area 2
network 66.66.66.0 0.0.0.255 area 2
network 192.168.66.0 0.0.0.255 area 2
area 2 range 168.168.168.0 255.255.255.192
area 2 authentication message-digest
!
ip nat inside source list 121 interface s0 overload
ip nat inside source static 192.168.66.100 150.50.46.100
access-list 121 permit ip 192.168.66.0 0.0.0.255 any
!
int tunnel 67
ip add 172.16.67.6 255.255.255.0
tunnel source 150.50.46.6
tunnel destination 150.50.57.7
!
router rip
version 2
no auto-summary
network 172.16.67.0
network 192.168.66.0
!
line con 0
no login
line vty 0 4
login
password hello

r7config
-----
r7#
hostname r7

```

```
!  
service password-encryption  
logging buffered 10000 7  
logging 150.50.15.101  
logging facility local6  
no service tcp-small-server  
no service udp-small-server  
no service finger  
service debug timestamp  
no ntp enable  
no cdp run  
ip http server  
ip http access-class 10  
access-list 10 permit 150.50.0.0 0.0.255.255  
snmp-server community hello ro 71  
snmp-server community hellorw rw 72  
snmp-server contact Hello Computers  
snmp-server location Fremont-Santa Clara  
access-list 71 permit 150.50.0.0 0.0.255.255  
access-list 72 permit 150.50.111.0 0.0.0.255  
scheduler interval 1000  
no ip domain-lookup  
no ip source-route  
!  
!acl for icmp rate-limiting  
access-list 141 permit icmp any any  
access-list 141 deny ip any any  
!  
!deny Trinoo  
access-list 171 deny tcp any any eq 27665  
access-list 171 deny udp any any eq 31335  
access-list 171 deny udp any any eq 26444  
!deny Stacheldraht  
access-list 171 deny tcp any any eq 16660  
access-list 171 deny tcp any any eq 65000  
!deny subseven  
access-list 171 deny tcp any any eq 6711  
access-list 171 deny tcp any any eq 6712  
access-list 171 deny tcp any any eq 6669  
access-list 171 deny tcp any any eq 2222  
access-list 171 deny tcp any any eq 7000  
access-list 171 permit ip any any  
!  
enable secret hello  
!  
int e0  
no ip directed-broadcast  
no ip proxy-arp  
no ip redirects  
no ip icmp mask-reply  
no ip icmp unreachable  
no ip route-cache  
rate-limit output access-group 141 1000000 512000 786000 conform-action transmit exceed-action drop
```

```
ip access-group 171 out
ip add 10.10.77.7 255.255.255.0
no shut
ip nat inside
!
int s0
encapsulation hdlc
clock rate 64000
ip address 150.50.57.7 255.255.255.0
no shut
ip nat outside
!
int lo0
ip add 77.77.77.77 255.255.255.0
!
router eigrp 57
no auto-summary
network 150.50.57.0 0.0.0.255
network 77.77.77.0 0.0.0.255
network 10.10.77.0 0.0.0.255
!
ip nat inside source list 121 interface s0 overload
ip nat inside source static 10.10.77.100 150.50.57.100
access-list 121 permit ip 10.10.77.0 0.0.0.255 any
!
int tunnel 76
ip add 172.16.67.7 255.255.255.0
tunnel source 150.50.57.7
tunnel destination 150.50.46.6
!
router rip
version 2
no auto-summary
network 172.16.67.0
network 10.10.77.0
!
line con 0
no login
!
line vty 0 4
login
password hello

catconfig
-----
cat(enable)

set vtp domain hello
set vtp mode transparent
!
set port name 3/1 r1e0
set port name 3/2 r2e0
set port name 3/3 r3e0
```

```
set port name 3/4 r4e0
set port name 3/5 r5e0
set port name 3/6 r6e0
set port name 3/7 r7e0
set port name 3/8 bb1e0
set port name 3/9 bb2e0
set port name 3/10 bb3e0
set port name 3/11 pix1e0
set port name 3/12 pix1e1
set port name 3/13 pix1e2
set port name 3/14 pix2e0
set port name 3/15 pix2e1
set port name 3/16 solaris1
set port name 3/17 solaris2
set port name 3/18 tacacs-ca
set port name 3/19 tftp
!
set vlan 3 3/3
set vlan 6 3/6
set vlan 7 3/7
set vlan 11 3/13
set vlan 15 3/1,3/5,3/11,3/16
set vlan 24 3/2,3/4,3/14,3/17
set vlan 111 3/8,3/12,3/18-19
set vlan 112 3/9,3/15
set vlan 113 3/10
!
set port speed 3/1 auto
set port duplex 3/1 auto
set port speed 3/2 auto
set port duplex 3/2 auto
set port speed 3/3 auto
set port duplex 3/4 auto
set port speed 3/5 auto
set port duplex 3/6 auto
set port speed 3/7 auto
set port duplex 3/7 auto
set port speed 3/8 auto
set port duplex 3/8 auto
set port speed 3/9 auto
set port duplex 3/9 auto
set port speed 3/10 auto
set port duplex 3/10 auto
set port speed 3/11 auto
set port duplex 3/11 auto
set port speed 3/12 auto
set port duplex 3/12 auto
set port speed 3/13 auto
set port duplex 3/13 auto
set port speed 3/14 auto
set port duplex 3/14 auto
set port speed 3/15 auto
set port duplex 3/15 auto
```

```

set port speed 3/16 auto
set port duplex 3/16 auto
set port speed 3/17 auto
set port duplex 3/17 auto
set port speed 3/18 auto
set port duplex 3/18 auto
!
set vlan 111 name backbone1
set vlan 112 name backbone2
set vlan 113 name backbone3
set vlan 15 name pix1outsidevlan
set vlan 7 name r7e0vlan
set vlan 6 name r6e0vlan
set vlan 4 name r4e0vlan
set vlan 22 name pix2outsidevlan
set vlan 11 name pix1dmzvlan
!
set interface sc0 150.50.111.90 255.255.255.0
set interface sc0 111
set ip route default 150.50.111.11 primary
!
set ip permit enable
set ip permit 150.50.0.0 255.255.0.0
!
set port security 3/1 0000.0c76.443a shut 60 violation shutdown
set port security 3/2 0010.7b7f.c207 shut 60 violation shutdown
!
set port span 3/4 3/20 both
!
set security acl ip vlan6iponly permit ip any any
commit security acl vlan6iponly
set security acl map vlan6iponly 6
!

pix1config
-----
pix1(config)#
!
hostname pix1
interface e0 auto
interface e1 auto
interface e2 auto
!
nameif e0 outside sec0
nameif e1 inside sec100
nameif e2 dmz sec50
!
ip address outside 150.50.15.11 255.255.255.0
ip address inside 150.50.111.11 255.255.255.0
ip address dmz 10.10.11.11 255.255.255.0
!
nat (inside) 0 access-list nonat
access-list nonat permit ip 150.50.111.0 255.255.255.0 10.10.11.0 255.255.255.0

```

```

!
nat (inside) 1 0 0
global (outside) 1 150.50.15.150-150.50.15.160 255.255.255.0
global (outside) 1 150.50.111.50
!
rip outside passive version 2
rip outside default version 2
!
route outside 0 0 150.50.15.1
!
!static and conduit for router bb1 to allow BGP connection from r1
static (inside,outside) 150.50.15.111 150.50.111.111
conduit permit tcp host 150.50.15.111 gt 11000 host 150.50.15.1
!
!static and conduit for aaa/ca server
static (inside,outside) 150.50.15.100 150.50.111.100
conduit permit ip host 150.50.15.100 0 0
!
!static and conduit for tftp server
static (inside,outside) 150.50.15.101 150.50.111.101
conduit permit tcp host 150.50.15.101 eq tftp 0 0
!
aaa-server TACACS+ protocol tacacs+
aaa-server AuthOutbound protocol tacacs+
aaa-server AuthOutbound (inside) host 150.50.111.100 hello timeout 5
aaa authentication include ftp outbound 0 0 0 0 AuthOutbound
!
filter url http 0 0 0 0 allow
url-server (inside) host 150.50.111.101 timeout 10
!
ip local pool pptp-pool 192.168.1.0-192.168.1.254
nat (inside) 0 access-list nonat
access-list nonat permit ip 150.50.111.0 255.255.255.0 192.168.1.0 255.255.255.0
!
vpdn group 1 accept dialin pptp
vpdn group 1 ppp authentication pap
vpdn group 1 ppp authentication chap
vpdn group 1 ppp authentication mschap
vpdn group 1 client configuration address local pptp-pool
vpdn group 1 client authentication local
vpdn username hello password hello
vpdn enable outside
!notes for pptp client config: configure win2k pro and make new network connection, select vpn option, uncheck box
under security that says require data encryption, provide username and password hello and click on connect.
!
!
pix2config
-----
hostname pix2
!
interface e0 auto
interface e1 auto
!

```

```
nameif e0 outside sec0
nameif e1 inside sec100
!
ip address outside 150.50.24.12 255.255.255.0
ip address inside 10.10.112.12 255.255.255.0
!
nat (inside) 1 150.50.111.0 255.255.255.0
global (outside) 1 150.50.24.150-150.50.24.160 255.255.255.0
global (outside) 1 150.50.24.50
!
rip outside passive version 2 authentication md5 hello 1
rip outside default version 2 authentication md5 hello 1
!
route outside 0 0 150.50.24.2
route inside 112.112.112.0 255.255.255.0 10.10.112.112
!
!static and conduit to allow ping to bb2 loopback0 from r2
static (inside,outside) 150.50.24.113 112.112.112.112
conduit permit icmp host 150.50.24.113 host 150.50.22.2
!
!static and conduit to allow gre traffic to bb2 from r2
static (inside,outside) 150.50.24.112 10.10.112.112
conduit permit gre host 150.50.24.112 host 150.50.24.2
!
nat (inside) 0 10.10.112.120 255.255.255.255
!
conduit permit tcp host 150.50.24.112 eq telnet host 150.50.24.150
conduit permit tcp host 150.50.24.113 eq telnet host 150.50.15.111
!
!
```